

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 02/02/2023 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Article
Product name : 427/B552 - METALASTIC BLACK BITUMINIOUS PAINT
Product code : 10645
Type of product : Paint
Product group : End product
Other means of identification : 427/B552/3

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Teal & Mackrill (Pty) Ltd.
Lockwood Street
Hull – East Yorkshire HU2 0HN
England
T +44 (0)1482 320194
info@teamac.co.uk

Distributor

Teal & Mackrill EU B.V.
Queens Towers
Delflandlaan 1
1062 EA Amsterdam
Netherlands
T +31 (0)208 004828
info@teamac.co.uk

1.4. Emergency telephone number

Emergency number : +44 (0) 1482 320194 Teamac (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3	H226
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity – Repeated exposure, Category 1	H372
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

GHS09

Signal word (CLP) :

Danger

Contains :

NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY; LOW BOILING

427/B552 - METALASTIC BLACK BITUMINIOUS PAINT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP)	: H226 - Flammable liquid and vapour. H336 - May cause drowsiness or dizziness. H372 - Causes damage to organs through prolonged or repeated exposure. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P314 - Get medical advice/attention if you feel unwell. P370+P378 - In case of fire: Use media other than water to extinguish. P403+P235 - Store in a well-ventilated place. Keep cool. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY; LOW BOILING substance with national workplace exposure limit(s) (GB)	CAS-No.: 64742-82-1 EC-No.: 919-446-0 REACH-no: 01-2119458049-33	$\geq 30 - < 50$	Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Get medical advice/attention if you feel unwell. Never give anything by mouth to an unconscious person.
First-aid measures after inhalation	: Move the affected person away from the contaminated area and into the fresh air. Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Take off immediately all contaminated clothing. Wash skin with plenty of water.
First-aid measures after eye contact	: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Do not induce vomiting. Obtain emergency medical attention.

427/B552 - METALASTIC BLACK BITUMINIOUS PAINT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂).

5.2. Special hazards arising from the substance or mixture

Fire hazard : Vapours may cause fire/explosion if source of ignition is present.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Prevent fire fighting water from entering the environment. Use water spray or fog for cooling exposed containers.
Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin and eyes. No flames, no sparks. Eliminate all sources of ignition.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Do not allow to enter drains or water courses. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage. Absorb spilled material with sand or earth.
Methods for cleaning up : Absorb remaining liquid with sand or inert absorbent and remove to safe place. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

427/B552 - METALASTIC BLACK BITUMINIOUS PAINT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

- Precautions for safe handling : Avoid contact with skin and eyes. Do not breathe vapours. Do not eat, drink or smoke when using this product. Ensure good ventilation of the work station. Handle and open container with care. Keep away from sources of ignition - No smoking.
- Hygiene measures : Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR. Up to 250 litres of liquids with a flashpoint above 32C but below 55C may be kept in a workroom provided they are kept in closed containers in a marked, fire-resisting cupboard or bin. Larger quantities must be kept in a separate, marked storeroom conforming to the structural requirements contained in the HSE guidance note Storage of Flammable Liquids in Containers.
- Storage conditions : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed.
- Incompatible products : Oxidizing agent. Strong acids. Strong bases.
- Storage temperature : 5 – 25 °C
- Storage area : Store away from heat.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY; LOW BOILING (64742-82-1)

United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA) [1]	250 mg/m ³ Vapour
-----------------------	------------------------------

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Provide local exhaust or general room ventilation.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



427/B552 - METALASTIC BLACK BITUMINIOUS PAINT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves against chemicals (EN 374). Nitrile rubber gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Do not exceed the occupational exposure limits (OEL).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Black.
Appearance	: Viscous liquid. Dark coloured liquid.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Above 150°C
Flammability	: 0.6 – 8 % volume
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: min 32°C Closed cup.
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not applicable.
Viscosity, kinematic	: > 20.5 mm ² /s
Solubility	: Not miscible.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 0.9 – 0.95 @ 20 °C
Relative vapour density at 20°C	: > 1 g/m ³
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : < 385 g/l

427/B552 - METALASTIC BLACK BITUMINIOUS PAINT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Oxidizing agent. Strong bases. Strong acids.

10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified pH: Not applicable.
Serious eye damage/irritation	: Not classified pH: Not applicable.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY; LOW BOILING (64742-82-1)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.

NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY; LOW BOILING (64742-82-1)

STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
------------------------	---

Aspiration hazard : Not classified

427/B552 - METALASTIC BLACK BITUMINIOUS PAINT

Viscosity, kinematic	> 20.5 mm ² /s
----------------------	---------------------------

11.2. Information on other hazards

No additional information available

427/B552 - METALASTIC BLACK BITUMINIOUS PAINT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.
Not rapidly degradable

12.2. Persistence and degradability

427/B552 - METALASTIC BLACK BITUMINIOUS PAINT

Persistence and degradability	The product is not expected to be biodegradable.
-------------------------------	--

12.3. Bioaccumulative potential

427/B552 - METALASTIC BLACK BITUMINIOUS PAINT

Bioaccumulative potential	No bioaccumulation data available.
---------------------------	------------------------------------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

427/B552 - METALASTIC BLACK BITUMINIOUS PAINT

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Results of PBT assessment	This product does not contain any substances classified as PBT or vPvB.
---------------------------	---

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Other adverse effects : This product contains Volatile Organic Compounds (VOCs) which have a photochemical ozone creation potential.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials : Avoid release to the environment.
European List of Waste (LoW) code : 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances
15 01 02 - plastic packaging
If mixed with other wastes, the above waste code may not be applicable.

427/B552 - METALASTIC BLACK BITUMINIOUS PAINT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

HP Code

- : HP3 - "Flammable:"
 - flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
 - flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
 - flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
 - flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
 - water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
 - other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
- HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.
- HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1263	UN 1263	UN 1263	Not applicable	UN 1263
14.2. UN proper shipping name				
PAINT RELATED MATERIAL (PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound))	PAINT (PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound))	Paint (PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound))	Not applicable	PAINT (PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound))
Transport document description				
UN 1263 PAINT RELATED MATERIAL (PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)), 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT (PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)), 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1263 Paint (PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)), 3, III, ENVIRONMENTALLY HAZARDOUS	Not applicable	UN 1263 PAINT (PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)), 3, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
3	3	3	Not applicable	3
			Not applicable	

427/B552 - METALASTIC BLACK BITUMINIOUS PAINT


Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.4. Packing group				
III	III	III	Not applicable	III
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Not applicable	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 163, 367, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	: 
Tunnel restriction code (ADR)	: D/E
EAC code	: •3Y

Transport by sea

Special provisions (IMDG)	: 163, 223, 367, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

427/B552 - METALASTIC BLACK BITUMINIOUS PAINT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Inland waterway transport

Not applicable

Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 163, 367, 650
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T2
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

14.7. Maritime transport in bulk according to IMO instruments

IBC code : Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Not applicable.

REACH Annex XIV (Authorisation List)

Not applicable.

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : < 385 g/l

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

United Kingdom

British National Regulations : The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716.

427/B552 - METALASTIC BLACK BITUMINIOUS PAINT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ATE	Acute Toxicity Estimate
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
DNEL	Derived-No Effect Level
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
VOC	Volatile Organic Compounds
PBT	Persistent Bioaccumulative Toxic
vPvB	Very Persistent and Very Bioaccumulative

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.