



TECHNICAL DATA SHEET 2 PACK ZINC PHOSPHATE THINNERS EVT-455

TDS: TMQ60739 **600/Q607/39**

DESCRIPTION:

Thinners for 2 Pack Zinc Phosphate Primer.

RECOMMENDED USE:

As a thinner or cleaning agent

AVAILABILITY:

0.5 litres, 2.5 litres

FINISH:

N/A

COLOUR:

N/A

TYPICAL S.G. (SPECIFIC GRAVITY):

0.84 to 0.86 @ 20 °C

VOLUME SOLIDS:

N/A

WET FILM THICKNESS W.F.T

N/A

DRY FILM THICKNESS D.F.T

N/A

EXPECTED SPREADING RATE:

N/A

N/A

The practical spreading rate may be lower as this depends on factors such as the porosity and roughness of the surface to be painted and material losses during application.

TYPICAL VISCOSITY:

N/A

FLASH POINT:

21 °C (closed cup)

CURE TIME: @ RECOMMENDED D.F.T

Initial cure: N/A

Hard dry: N/A

Full cure: N/A

Low temperature and high humidity will adversely affect application, curing and performance of any coating.

POTLIFE:

N/A

Pot Life - Once the parts are mixed together the material has to be used within the time stated.

MINIMUM OVERCOATING TIME:

APPLICATION SPECIAL CONDITIONS:

N/A

VOC CONTENT:

g / litre

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution

APPLICATION DETAILS:

Application N/A

restrictions

Method: N/A N/A

N/A

Thinner

(Max vol):

Nozzle size: N/A

Nozzle

pressure:

Cleaning

N/A

solvent:

Recoat interval:

SURFACE PREPARATION:

For further advice contact Teamac Technical Services on +44(0)1482 320194

The physical constants are subject to normal manufacturing tolerances.

"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"

TEAMAC

Lockwood Street, Hull HU2 0HN
Tel.: +44(0)1482 320194. Fax: +44(0)1482 219266

Email: info@teamac.co.uk www.teamac.co.uk

Date printed 22 June 2015 Page 1 of 2

TECHNICAL DATA SHEET

TDS: TMQ60739 2 PACK ZINC PHOSPHATE THINNERS EVT-455 600/Q607/39

MIXING INSTRUCTIONS:

APPLICATION CONDITIONS:

FLAMMABILITY LIMIT - LOWER(%)=0.8

PRECEDING COAT:

N/A

SUBSEQUENT COAT:

N/A

REMARKS:

HEALTH AND SAFETY:

See safety data sheet - SDS 10977

ISSUED:

22 June 2015

REVISION:

2

The information given in this data sheet is based on experience and is accurate to the best of our knowledge. No guarantee should be implied, however, as the conditions of use are beyond our control. This data sheet does not constitute a specificaton. In case of doubt as to the suitability of the product please contact our Technical Service Department on 01482 320194.

> For further advice contact Teamac Technical Services on +44(0)1482 320194 The physical constants are subject to normal manufacturing tolerances.

> > "COVERING OUR CUSTOMERS' NEEDS SINCE 1908"

TEAMAC

Lockwood Street, Hull HU2 0HN Tel.: +44(0)1482 320194. Fax: +44(0)1482 219266 Email: info@teamac.co.uk www.teamac.co.uk

Date printed 22 June 2015 Page 2 of 2