

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 25/04/2023 Revision date: 01/02/2024 Supersedes version of: 25/04/2023 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Product name	: 414-G770 - RAPIDRY ANTI CORROSIVE FINISH - TBL BASE
UFI	: HSXP-W2GX-800C-2D9W
Product code	: 20845
Type of product	: Paint
Product group	: Blend
Other means of identification	: 414/G770/B

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

No additional information available

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Teal & Mackrill Ltd
Lockwood Street
Hull, East Yorkshire, HU2 0HN
England
T +44 (0)1482 320194
info@teamac.co.uk

Distributor

Teal & Mackrill EU B.V.
Queens Towers
Delflandlaan 1
1062 EA Amsterdam
Netherlands
T +31 (0)208 004828
info@teamac.co.uk

1.4. Emergency telephone number

Emergency number : +44 (0) 1482 320194 Teamac (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3	H226
Acute toxicity (dermal), Category 4	H312
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity – Repeated exposure, Category 2	H373
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

414-G770 - RAPIDRY ANTI CORROSIVE FINISH - TBL BASE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Warning

Contains

: xylene; ethylbenzene

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.
H312 - Harmful in contact with skin.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H335 - May cause respiratory irritation.
H373 - May cause damage to organs through prolonged or repeated exposure.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH-statements

: EUH208 - Contains NEODECANOATE ACID, COBALT SALT (27253-31-2) (20313). May produce an allergic reaction.
EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

414-G770 - RAPIDRY ANTI CORROSIVE FINISH - TBL BASE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Xylene isomer mixture (self classification) substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216-32	≥ 30 – < 50	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Titanium Dioxide substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 13463-67-7 EC-No.: 236-675-5 REACH-no: 01-2119489379-17	≥ 10 – < 30	Not classified
Calcium Carbonate substance with national workplace exposure limit(s) (CZ, SK); substance with a Community workplace exposure limit	CAS-No.: 1317-65-3 EC-No.: 215-279-6	≥ 5 – < 10	Not classified
Diatomaceous Earth substance with national workplace exposure limit(s) (GB)	CAS-No.: 61790-53-2 EC-No.: 310-127-6	≥ 1 – < 5	Not classified
ETHYLBENZENE	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4	≥ 1 – < 5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) STOT RE 2, H373 Asp. Tox. 1, H304
TRIZINC BIS(ORTHOPHOSPHATE)	CAS-No.: 7779-90-0 EC-No.: 231-944-3 EC Index-No.: 030-011-00-6 REACH-no: 01-2119485044-40	≥ 1 – < 5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Organoclay substance with national workplace exposure limit(s) (CZ, GB, SK); substance with a Community workplace exposure limit	CAS-No.: 68953-58-2 EC-No.: 273-219-4	< 1	Not classified
NEODECANOATE ACID, COBALT SALT substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 27253-31-2 EC-No.: 248-373-0	< 1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Skin Sens. 1, H317 Repr. 2, H361f Aquatic Chronic 3, H412
TOLUENE	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3 REACH-no: 01-2119471310-51	< 1	Flam. Liq. 2, H225 Repr. 2, H361d Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336

414-G770 - RAPIDRY ANTI CORROSIVE FINISH - TBL BASE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Strontium bis(2-ethylhexanoate)	CAS-No.: 2457-02-5 EC-No.: 219-536-3 REACH-no: 01-2120783571-49	< 1	Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 1B, H360Fd
Dipropylene Glycol Methyl Ether substance with national workplace exposure limit(s) (GB)	CAS-No.: 34590-94-8 EC-No.: 252-104-2 REACH-no: 01-2119450011-60	< 1	Not classified

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Seek medical attention immediately.
First-aid measures after inhalation	: Move the affected person away from the contaminated area and into the fresh air. Administer oxygen if breathing is difficult.
First-aid measures after skin contact	: Rinse skin with water/shower.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Rinse mouth thoroughly with water. If the person is fully conscious, make him/her drink water. Never give an unconscious person anything to drink. Do NOT induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Inhalation may cause irritation (cough, short breathing, difficulty in breathing).
Symptoms/effects after skin contact	: Prolonged or repeated contact may cause skin to become dry.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: dry chemical powder, alcohol-resistant foam, carbon dioxide (CO ₂).
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Explosion hazard	: Heating may cause an explosion.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Precautionary measures fire	: Evacuate area. Keep container tightly closed and away from heat, sparks and flame.
Protection during firefighting	: Use self-contained breathing apparatus and chemically protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Clear all other personnel from the area.
------------------	--

414-G770 - RAPIDRY ANTI CORROSIVE FINISH - TBL BASE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area. Do not touch or walk on the spilled product.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent liquid from entering sewers, watercourses, underground or low areas.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Collect spillage.
Methods for cleaning up : Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Large spills: scoop solid spill into closing containers.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Section 8. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wear personal protective equipment. Do not eat, drink or smoke when using this product. Do not handle until all safety precautions have been read and understood.
Hygiene measures : Always wash hands after handling the product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in original container. Store in a closed container.
Storage area : Bund storage facilities to prevent soil and water pollution in the event of spillage.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Titanium Dioxide (13463-67-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	10 mg/m ³ Inhalable dust
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	10 mg/m ³ Inhalable dust
Diatomaceous Earth (61790-53-2)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	1.2 mg/m ³ respirable dust
Xylene isomer mixture (self classification) (1330-20-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	50 ppm

414-G770 - RAPIDRY ANTI CORROSIVE FINISH - TBL BASE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Xylene isomer mixture (self classification) (1330-20-7)	
IOEL STEL	442 mg/m ³
	100 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	220 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	441 mg/m ³
	100 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
United Kingdom - Biological limit values	
BMGV	≈ 650 mmol/mol Creatinine
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Organoclay (68953-58-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	10 mg/m ³ Inhalable dust
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	10 mg/m ³ Inhalable dust
Calcium Carbonate (1317-65-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	10 mg/m ³ Inhalable Dust
NEODECANOATE ACID, COBALT SALT (27253-31-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	0.1 mg/m ³
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	0.1 mg/m ³
Dipropylene Glycol Methyl Ether (34590-94-8)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	308 mg/m ³
	50 ppm

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

414-G770 - RAPIDRY ANTI CORROSIVE FINISH - TBL BASE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Provide local exhaust or general room ventilation. Personal, workplace, environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Ensure control measures are regularly inspected and maintained.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Wear eye protection

8.2.2.2. Skin protection

Hand protection:

As a general principal, exposure should be managed by means other than the provision of protective gloves. Permeation time: minimum >480min long term exposure; material / thickness [mm]: Protective gloves against chemicals (EN 374)

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Keep container tightly closed. Do not exceed the occupational exposure limits (OEL).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: white. off-white.
Appearance	: Viscous liquid. Coloured liquid.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 26 approx. °C Closed cup.
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Technically not feasible.
Viscosity, kinematic	: > 20.5 mm ² /s
Viscosity, dynamic	: 2 – 2.2 P @20°C
Solubility	: immiscible.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available

414-G770 - RAPIDRY ANTI CORROSIVE FINISH - TBL BASE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Density	: Not available
Relative density	: 1.19 @ 20°C
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : < 485 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

Stable under normal conditions of use.

10.4. Conditions to avoid

Avoid open fire or flames. Heat.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Harmful in contact with skin.
Acute toxicity (inhalation)	: Inhalation:dust,mist: Harmful if inhaled.

414-G770 - RAPIDRY ANTI CORROSIVE FINISH - TBL BASE	
ATE CLP (dermal)	1100 mg/kg bodyweight
ATE CLP (dust,mist)	3.702 mg/l/4h
Xylene isomer mixture (self classification) (1330-20-7)	
LD50 oral rat	3523 mg/kg
LD50 dermal rat	1100 mg/kg
TRIZINC BIS(ORTHOPHOSPHATE) (7779-90-0)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
Strontium bis(2-ethylhexanoate) (2457-02-5)	
LD50 oral rat	> 2000 mg/kg

414-G770 - RAPIDRY ANTI CORROSIVE FINISH - TBL BASE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Strontium bis(2-ethylhexanoate) (2457-02-5)

LD50 dermal rat	> 2000 mg/kg
Skin corrosion/irritation	: Causes skin irritation. pH: Technically not feasible.
Serious eye damage/irritation	: Causes serious eye irritation. pH: Technically not feasible.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.

Xylene isomer mixture (self classification) (1330-20-7)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

TOLUENE (108-88-3)

STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.

Xylene isomer mixture (self classification) (1330-20-7)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

TOLUENE (108-88-3)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

ETHYLBENZENE (100-41-4)

STOT-repeated exposure	May cause damage to organs (hearing organs) through prolonged or repeated exposure.
------------------------	---

TRIZINC BIS(ORTHOPHOSPHATE) (7779-90-0)

LOAEL (oral, rat, 90 days)	53.8 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	31.52 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

Aspiration hazard	: Not classified
-------------------	------------------

414-G770 - RAPIDRY ANTI CORROSIVE FINISH - TBL BASE

Viscosity, kinematic	> 20.5 mm ² /s
----------------------	---------------------------

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

Xylene isomer mixture (self classification) (1330-20-7)

LC50 - Fish [1]	2.6 mg/l Rainbow Trout
EC50 - Crustacea [1]	1 – 5 mg/l Daphnia Magnia
EC50 72h - Algae [1]	3 – 5 mg/l Algae

414-G770 - RAPIDRY ANTI CORROSIVE FINISH - TBL BASE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Xylene isomer mixture (self classification) (1330-20-7)

NOEC chronic crustacea	1.91 mg/l EC10 21 Day Daphnia Magnia
------------------------	--------------------------------------

12.2. Persistence and degradability

414-G770 - RAPIDRY ANTI CORROSIVE FINISH - TBL BASE

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Titanium Dioxide (13463-67-7)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Diatomaceous Earth (61790-53-2)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Xylene isomer mixture (self classification) (1330-20-7)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

TOLUENE (108-88-3)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

ETHYLBENZENE (100-41-4)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Organoclay (68953-58-2)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

TRIZINC BIS(ORTHOPHOSPHATE) (7779-90-0)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Calcium Carbonate (1317-65-3)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

NEODECANOATE ACID, COBALT SALT (27253-31-2)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Dipropylene Glycol Methyl Ether (34590-94-8)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Strontium bis(2-ethylhexanoate) (2457-02-5)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

414-G770 - RAPIDRY ANTI CORROSIVE FINISH - TBL BASE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.7. Other adverse effects

No additional information available






SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations	: Do not discharge into drains or rivers.
Product/Packaging disposal recommendations	: Discharging into rivers and drains is forbidden. Dispose in a safe manner in accordance with local/national regulations.
European List of Waste (LoW, EC 2000/532)	: 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances 15 01 02 - plastic packaging 15 01 04 - metallic packaging
HP Code	: HP3 - "Flammable:" – flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; – flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; – flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; – flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; – water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; – other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP6 - "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure. HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263
14.2. UN proper shipping name				
PAINT	PAINT	Paint	PAINT	PAINT
Transport document description				
UN 1263 PAINT, 3, III, (D/E)	UN 1263 PAINT, 3, III	UN 1263 Paint, 3, III	UN 1263 PAINT, 3, III	UN 1263 PAINT, 3, III
14.3. Transport hazard class(es)				
3	3	3	3	3
				

414-G770 - RAPIDRY ANTI CORROSIVE FINISH - TBL BASE


Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 163, 367, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	: 
Tunnel restriction code (ADR)	: D/E
EAC code	: •3Y

Transport by sea

Special provisions (IMDG)	: 163, 223, 367, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

414-G770 - RAPIDRY ANTI CORROSIVE FINISH - TBL BASE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 163, 367, 650
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 163, 367, 650
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T2
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

VOC Directive (2004/42)

VOC content : < 485 g/l

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

414-G770 - RAPIDRY ANTI CORROSIVE FINISH - TBL BASE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Toluene		108-88-3	2902 30 00	Category 3		Annex I

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DNEL	Derived-No Effect Level
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
SDS	Safety Data Sheet
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative
PBT	Persistent Bioaccumulative Toxic

Data sources

: ECHA (European Chemicals Agency). REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006. Supplier's safety documents.

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains NEODECANOATE ACID, COBALT SALT (27253-31-2) (20313). May produce an allergic reaction.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1

414-G770 - RAPIDRY ANTI CORROSIVE FINISH - TBL BASE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H360Fd	May damage fertility. Suspected of damaging the unborn child.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Repr. 1B	Reproductive toxicity, Category 1B
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.